



MATERIALS AND FINISH

SHELL : STEEL MATERIAL, FRONT SHELL NICKEL FINISHED
 BACK SHELL TIN FINISHED
 INSULATOR : PBT THERMOPLASTIC, 30% GLASS
 FILLED, UL 94V-0 RATED, WHITE COLOR
 CONTACT MATERIAL : BRASS
 CONTACT FINISH : FULL GOLD FLASH
 RIVETED INSERT : BRASS MATERIAL , NICKEL FINISHED
 JACK SCREWS : BRASS MATERIAL , NICKEL FINISHED

ELECTRICAL CHARACTERISTICS

CONTACT CURRENT RATING : 5.0 AMPS
 CONTACT RESISTANCE : 30 MILLIOHMS MAX.
 DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC MIN.
 INSULATION RESISTANCE : 5000 MEGAOHMS MIN.
 TEMPERATURE RATING : -55°C ~ +105°C

Drawn by	liuqiong	2002.05.10
Designed by	chajia	2002.05.10
Approved by	yangjinguo	2002.05.10
	Sheet 1 of 1	Code 000
Dimensions in mm(Inches)		Scale 1:1
Tolerances on:XX±.0.13		Angles±.2°

